

FACT SHEET

ANDAMAN

PRODUCT	COLOR / REF	SIZE	PACKING	
	ANDAMAN PLAIN SKU# AND-PLA	24.8x28.5cm (10"x11")	18 Pcs/Box 10.22 Sqft/Box 53 Lbs/Box 60 Boxes/Pallet 613.20 Sqft/Pallet	
	ANDAMAN DECOR SKU# AND-DEC	24.8x28.5cm (10"x11")	18 Pcs/Box 10.22 Sqft/Box 53 Lbs/Box 60 Boxes/Pallet 613.20 Sqft/Pallet	
ТҮРЕ	Glazed Porcelain			
APPLICATION	Indoors/Outdoors Wall/Floor			
DESCRIPTION	Worn-looking hexagonal porcelain floor tiles with a vintage appeal.			
PRODUCT INSTALLATION	It is recommended for the product to be installed by a qualified professional. We do not recommend the use of adhesives based on epoxy resin. Read carefully instructions set by the manufacturer of the adhesive used.			
PRODUCT CARE	For initial and daily cleaning the use of a damp cloth and mild soap is recommended. Avoid using abrasive and acidic cleaning products.			
* N O T E	To achieve the visual aspect of the product and given the artisanal procedure for production and raw materials used, pieces can represent variation in size, texture, design and shade. This is done deliberately to give the product a unique personality and unrepeatable characteristics.			



FACT SHEET

ANDAMAN

TECHN	ICAL SPECIFICATIONS	ISO	TEST METHOD	PASS/FAIL
	FROST RESISTANCE	ISO 10545-12	Resists	Yes

SURFACE TECHNICAL

S I	PECIFICATIONS	ISO	TEST METHOD	PASS/FAIL
L	ACID & ALKALI RESISTANCE	ISO 10545-13	GLA/GLA	Yes
}	CRAZING RESISTANCE	ISO 10545-11	Resists	Yes
	STAINING RESISTANCE	ISO 10545-14	5	Yes
-	SURFACE QUALITY	ISO 10545-2	> 95%	Yes