



## **ARTIST** COLOR / REF PACKING PRODUCT SIZE 20 Pcs/Box 10.65 Sqft/Box 53 Lbs/Box ARTIST BLUE STAR 22.3x22.3cm 60 Boxes/Pallet SKU# ART-BLU-STA (8.5"x8.5") 639 Sqft/Pallet 20 Pcs/Box 10.65 Sqft/Box ARTIST BLUE DIAGONALE 22.3x22.3cm 53 Lbs/Box SKU# ART-BLU-DIA (8.5"x8.5") 60 Boxes/Pallet 639 Sqft/Pallet 20 Pcs/Box 10.65 Sqft/Box ARTIST BLUE RHOMBUS 22.3x22.3cm 53 Lbs/Box SKU# ART-BLU-RHO (8.5"x8.5") 60 Boxes/Pallet 639 Sqft/Pallet 20 Pcs/Box 10.65 Sqft/Box 53 Lbs/Box ARTIST BLUE TRIANGLE 22.3x22.3cm 60 Boxes/Pallet SKU# ART-BLU-TRI (8.5"x8.5") 639 Sqft/Pallet



| ARTIST                  |  |  |  |  |  |
|-------------------------|--|--|--|--|--|
| TYPE                    | Glazed Porcelain   |  |  |  |  |
| APPLICATION             | Indoors/Outdoors Wall/Floor  |  |  |  |  |
| DESCRIPTION             | This collection has a strong Mediterranean flavor. Thanks to the white, blue and navy colors of its geometrical pattern, it evokes the charm of traditional hand painted tiles.  |  |  |  |  |
| PRODUCT<br>INSTALLATION | It is recommended for the product to be installed by a qualified professional. We do not recommend the use of adhesives based on epoxy resin. Read carefully instructions set by the manufacturer of the adhesive used.  |  |  |  |  |
| PRODUCT CARE            | For initial and daily cleaning the use of a damp cloth and mild soap is recommended.  Avoid using abrasive and acidic cleaning products.   |  |  |  |  |
| *NOTE                   | To achieve the visual aspect of the product and given the artisanal procedure for production and raw materials used, pieces can represent variation in size, texture, design and shade. This is done deliberately to give the product a unique personality and unrepeatable characteristics. |  |  |  |  |

| TECHNICAL SPECIFICATIONS |                  | ISO          | TEST METHOD | PASS/FAIL |
|--------------------------|------------------|--------------|-------------|-----------|
| 37 K                     | FROST RESISTANCE | ISO 10545-12 | Resists     | Yes       |

| SURFACE TECHNICAL SPECIFICATIONS |                             | 150          | TEST METHOD | PASS/FAIL |
|----------------------------------|-----------------------------|--------------|-------------|-----------|
|                                  | ACID & ALKALI<br>RESISTANCE | ISO 10545-13 | GLA/GLA     | Yes       |
| <b>}</b>                         | CRAZING<br>RESISTANCE       | ISO 10545-11 | Resists     | Yes       |
|                                  | STAINING<br>RESISTANCE      | ISO 10545-14 | 5           | Yes       |
| _                                | SURFACE QUALITY             | ISO 10545-2  | > 95%       | Yes       |