




LINS

PRODUCT	COLOR / REF	SIZE	PACKING
	LINS WHITE SKU# LIN-WHI	20x20cm (8"x8")	26 Pcs/Box 11.19 Sqft/Box 40 Lbs/box 72 Boxes/Pallet 805.68 Sqft/Pallet
	LINS MOONLIGHT SKU# LIN-MOO	20x20cm (8"x8")	26 Pcs/Box 11.19 Sqft/Box 40 Lbs/box 72 Boxes/Pallet 805.68 Sqft/Pallet
	LINS GREY SKU# LIN-GRE	20x20cm (8"x8")	26 Pcs/Box 11.19 Sqft/Box 40 Lbs/box 72 Boxes/Pallet 805.68 Sqft/Pallet
	LINS PUMPKIN LIN-PUM	20x20cm (8"x8")	26 Pcs/Box 11.19 Sqft/Box 40 Lbs/box 72 Boxes/Pallet 805.68 Sqft/Pallet

LINS

PRODUCT	COLOR / REF	SIZE	PACKING
	LINS TEAL SKU# LIN-TEA	20x20cm (8"x8")	26 Pcs/Box 11.19 Sqft/Box 40 Lbs/box 72 Boxes/Pallet 805.68 Sqft/Pallet
TYPE	Glazed Porcelain	APPLICATION	Indoors/Outdoors Wall/Shower Wall
DESCRIPTION	Lins playing with lines, creates visual effects perfect for transforming wall surfaces. Taking advantage of the linear grooves it creates a shadow play and volumes are generated by the delicacy of the lines.		
PRODUCT INSTALLATION	It is recommended for the product to be installed by a qualified professional. We do not recommend the use of adhesives based on epoxy resin. Read carefully instructions set by the manufacturer of the adhesive used.		
PRODUCT CARE	For initial and daily cleaning the use of a damp cloth and mild soap is recommended. Avoid using abrasive and acidic cleaning products.		

TECHNICAL SPECIFICATIONS	ISO	TEST METHOD	PASS/FAIL
 FROST RESISTANCE	ISO 10545-12	Resist	Yes

SURFACE TECH. SPEC.	ISO	TEST METHOD	PASS/FAIL
 ACID & ALKALI RESISTANCE	ISO 10545-13	GLA/GLA	Yes
 CRAZING RESISTANCE	ISO 10545-11	Resists	Yes
 STAINING RESISTANCE	ISO 10545-14	5	Yes
 SURFACE QUALITY	ISO 10545-2	> 95%	Yes