



| ORIGAMI                 |   |                       |   |  |  |  |  |  |
|-------------------------|---|-----------------------|---|--|--|--|--|--|
| PRODUCT                 | COLOR / REF   | SIZE                  | PACKING   |  |  |  |  |  |
|                         | ORIGAMI BLANCO<br>SKU# ORI-BLA  | 24.8x28.5cm (10"x11") | 18 Pcs/Box<br>10.22 Sqft/Box<br>53 Lbs/Box<br>60 Boxes/Pallet<br>613.20 Sqft/Pallet |  |  |  |  |  |
|                         | ORIGAMI NEGRO<br>SKU# ORI-NEG   | 24.8x28.5cm (10"x11") | 18 Pcs/Box<br>10.22 Sqft/Box<br>53 Lbs/Box<br>60 Boxes/Pallet<br>613.20 Sqft/Pallet |  |  |  |  |  |
|                         | ORIGAMI GRIS<br>SKU# ORI-GRI  | 24.8x28.5cm (10"x11") | 18 Pcs/Box<br>10.22 Sqft/Box<br>53 Lbs/Box<br>60 Boxes/Pallet<br>613.20 Sqft/Pallet |  |  |  |  |  |
| TYPE                    | Glazed Porcelain  | APPLICATION           | Indoors/Outdoors Wall/Floor   |  |  |  |  |  |
| DESCRIPTION             | This hexagonal tile collection is suitable for indoor walls and floors, including shower areas. Its three flat monochrome matt tiles come in a choice of white, grey or black.  |                       |   |  |  |  |  |  |
| PRODUCT<br>INSTALLATION | It is recommended for the product to be installed by a qualified professional. We do not recommend the use of adhesives based on epoxy resin. Read carefully instructions set by the manufacturer of the adhesive used. |                       |   |  |  |  |  |  |
| PRODUCT CARE            | For initial and daily cleaning the use of a damp cloth and mild soap is recommended.  Avoid using abrasive and acidic cleaning products.  |                       |   |  |  |  |  |  |





| ORIGAMI                                |                  |              |             |           |  |  |
|--|------------------|--------------|-------------|-----------|--|--|
| TECHNICAL SPECIFICATIONS               |                  | ISO          | TEST METHOD | PASS/FAIL |  |  |
| ************************************** | FROST RESISTANCE | ISO 10545-12 | Resist      | Yes       |  |  |

| SURFACE TECHNICAL<br>SPECIFICATIONS |                             | ISO          | TEST METHOD | PASS/FAIL |
|-------------------------------------|-----------------------------|--------------|-------------|-----------|
|                                     | ACID & ALKALI<br>RESISTANCE | ISO 10545-13 | GLA/GLA     | Yes       |
| <b>3</b>                            | CRAZING<br>RESISTANCE       | ISO 10545-11 | Resists     | Yes       |
|                                     | STAINING<br>RESISTANCE      | ISO 10545-14 | 5           | Yes       |
|                                     | SURFACE QUALITY             | ISO 10545-2  | > 95%       | Yes       |