










PLYMOUTH

PRODUCT	COLOR / REF	SIZE	PACKING
	PLYMOUTH WHITE SKU# ARG-PLY-WHI	5x25cm (2"x10")	40 Pcs/Box 5.38 Sqft/Box 19 Lbs/Box 120 Boxes/Pallet 645.60 Sqft/Pallet
	PLYMOUTH PEARL SKU# ARG-PLY-PEA	5x25cm (2"x10")	40 Pcs/Box 5.38 Sqft/Box 19 Lbs/Box 120 Boxes/Pallet 645.60 Sqft/Pallet
	PLYMOUTH LATTE SKU# ARG-PLY-LAT	5x25cm (2"x10")	40 Pcs/Box 5.38 Sqft/Box 19 Lbs/Box 120 Boxes/Pallet 645.60 Sqft/Pallet
	PLYMOUTH SMOKE SKU# ARG-PLY-SMO	5x25cm (2"x10")	40 Pcs/Box 5.38 Sqft/Box 19 Lbs/Box 120 Boxes/Pallet 645.60 Sqft/Pallet

PLYMOUTH

TYPE	White body ceramic tile
APPLICATION	Indoors Wall/Shower Wall
DESCRIPTION	Argila Plymouth with semi-handcrafted appearance, comes in an innovative size. Its modularity and glossy tile and finish is what gives it its distinctive personality.
PRODUCT INSTALLATION	It is recommended for the product to be installed by a qualified professional. We do not recommend the use of adhesives based on epoxy resin. Read carefully instructions set by the manufacturer of the adhesive used.
PRODUCT CARE	For initial and daily cleaning the use of a damp cloth and mild soap is recommended. Avoid using abrasive and acidic cleaning products.
* NOTE	To achieve the visual aspect of the product and given the artisanal procedure for production and the natural stone used, pieces can represent variation in size, texture, design and shade. This is done deliberately to give the product a unique personality and unrepeatable characteristics.

	TECHNICAL SPECIFICATIONS	ISO	TEST METHOD	PASS/FAIL
	FROST RESISTANCE	ISO 10545-12	No Resist	Yes

	SURFACE TECHNICAL SPECIFICATIONS	ISO	TEST METHOD	PASS/FAIL
	ACID & ALKALI RESISTANCE	ISO 10545-13	GLA/GLA	Yes
	CRAZING RESISTANCE	ISO 10545-11	Resists	Yes
	STAINING RESISTANCE	ISO 10545-14	5	Yes
	SURFACE QUALITY	ISO 10545-2	> 95%	Yes