









POITIERS

PRODUCT	COLOR / REF	SIZE	PACKING
	<p>POITIERS WHITE SKU# ARG-POI-WHI</p>	<p>7.5x30cm (3"x12")</p>	<p>44 Pcs/Box 10.65 Sqft/Box 33 Lbs/box 60 Boxes/Pallet 639 Sqft/Pallet</p>
	<p>POITIERS MOONLIGHT SKU# ARG-POI-MOO</p>	<p>7.5x30cm (3"x12")</p>	<p>44 Pcs/Box 10.65 Sqft/Box 33 Lbs/box 60 Boxes/Pallet 639 Sqft/Pallet</p>
	<p>POITIERS LATTE SKU# ARG-POI-LAT</p>	<p>7.5x30cm (3"x12")</p>	<p>44 Pcs/Box 10.65 Sqft/Box 33 Lbs/box 60 Boxes/Pallet 639 Sqft/Pallet</p>
	<p>POITIERS SMOKE SKU# ARG-POI-SMO</p>	<p>7.5x30cm (3"x12")</p>	<p>44 Pcs/Box 10.65 Sqft/Box 33 Lbs/box 60 Boxes/Pallet 639 Sqft/Pallet</p>
	<p>POITIERS ROSE SKU# ARG-POI-ROS</p>	<p>7.5x30cm (3"x12")</p>	<p>44 Pcs/Box 10.65 Sqft/Box 33 Lbs/box 60 Boxes/Pallet 639 Sqft/Pallet</p>

POITIERS

TYPE	White body ceramic tile.
APPLICATION	Indoors Wall/Shower Wall
DESCRIPTION	This reinterpretation of a brick surface combines a handcrafted appearance with the characteristic shine of glass glazed tile.
PRODUCT INSTALLATION	It is recommended for the product to be installed by a qualified professional. We do not recommend the use of adhesives based on epoxy resin. Read carefully instructions set by the manufacturer of the adhesive used.
PRODUCT CARE	For initial and daily cleaning the use of a damp cloth and mild soap is recommended. Avoid using abrasive and acidic cleaning products.
* NOTE	To achieve the visual aspect of the product and given the artisanal procedure for production and the natural stone used, pieces can represent variation in size, texture, design and shade. This is done deliberately to give the product a unique personality and unrepeatable characteristics.

TECHNICAL SPECIFICATIONS		ISO	TEST METHOD	PASS/FAIL
	FROST RESISTANCE	ISO 10545-12	No Resist	Yes

SURFACE TECHNICAL SPECIFICATIONS		ISO	TEST METHOD	PASS/FAIL
	ACID & ALKALI RESISTANCE	ISO 10545-13	GLA/GLA	Yes
	CRAZING RESISTANCE	ISO 10545-11	Resists	Yes
	STAINING RESISTANCE	ISO 10545-14	5	Yes
	SURFACE QUALITY	ISO 10545-2	> 95%	Yes