





PEBBLE

PRODUCT	COLOR / REF	SIZE	PACKING
	<p>PEBBLE WHITE SKU# PEB-WHI-306</p>	<p>30x60cm (12"x24")</p>	<p>8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet</p>
	<p>PEBBLE WHITE SKU# PEB-WHI-606</p>	<p>60x60cm (24"x24")</p>	<p>8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet</p>
	<p>PEBBLE WHITE SKU# PEB-WHI-612</p>	<p>60x120cm (24"x48")</p>	<p>2 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet</p>
	<p>PEBBLE SABBIA SKU# PEB-SAB-306</p>	<p>30x60cm (12"x24")</p>	<p>8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet</p>

PEBBLE


PRODUCT	COLOR / REF	SIZE	PACKING
	<p>PEBBLE SABBIA SKU# PEB-SAB-606</p>	<p>60x60cm (24"x24")</p>	<p>8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet</p>
	<p>PEBBLE SABBIA SKU# PEB-SAB-612</p>	<p>60x120cm (24"x48")</p>	<p>2 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet</p>
	<p>PEBBLE GREY SKU# PEB-GRE-306</p>	<p>30x60cm (12"x24")</p>	<p>8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet</p>
	<p>PEBBLE GREY SKU# PEB-GRE-606</p>	<p>60x60cm (24"x24")</p>	<p>8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet</p>

PEBBLE

PRODUCT	COLOR / REF	SIZE	PACKING
	<p>PEBBLE GREY SKU# PEB-GRE-612</p>	<p>60x120cm (24"x48")</p>	<p>2 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet</p>
	<p>PEBBLE ANTRACITA SKU# PEB-ANT-306</p>	<p>30x60cm (12"x24")</p>	<p>8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet</p>
	<p>PEBBLE ANTRACITA SKU# PEB-ANT-606</p>	<p>60x60cm (24"x24")</p>	<p>8 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet</p>
	<p>PEBBLE ANTRACITA SKU# PEB-ANT-612</p>	<p>60x120cm (24"x48")</p>	<p>2 Pcs/Box 15.49 Sqft/Box 66 Lbs/Box 40 Boxes/Pallet 619.60 Sqft/Pallet</p>

PEBBLE

TYPE	Glazed Porcelain	APPLICATION	Indoors / Outdoors / Wall / Floor
DESCRIPTION	A product that stands out for its strong personality and modern design, Pebble fits in with the latest design concepts in the architecture and construction worlds, uniting two architectural materials and trendsetting looks that play a fundamental role in the building industry: stone and cement. Thanks to its choice of four colours, this urban-look collection is perfect for modern living spaces generally, fitting in with a wide variety of decorative styles.		
PRODUCT INSTALLATION	It is recommended for the product to be installed by a qualified professional. We do not recommend the use of adhesives based on epoxy resin. Read carefully the instructions set by the manufacturer of the adhesive used.		
PRODUCT CARE	For initial and daily cleaning the use of a damp cloth and mild soap is recommended. Avoid using abrasive and acidic cleaning products.		
NOTE	To achieve the visual aspect of the product and given the artisanal procedure for production and raw materials used, pieces can represent variation in size, texture, design and shade. This is done deliberately to give the product a unique personality and unrepeatable characteristics.		

TECHNICAL SPECIFICATIONS	ISO	TEST METHOD	PASS/FAIL
 FROST RESISTANCE	ISO 10545-12	No Resist	Pass

PEBBLE

CARACTERÍSTICAS TÉCNICAS Technical characteristics		NORMA DE ENSAYO TEST ESTANDAR UNE-ISO-10545	NORMA DE PRODUCTO PRODUCT STANDARD ISO 13006	VALORES PROMEDIA THE TILE COMPANY THE TILE COMPANY AVERAGE VALUES
	LONGITUD Y ANCHURA Length and width	10545-2	± 0.6%	± 0.1%
	GROSOR Thickness		± 5.0%	± 5.0%
	RECTITUD DE LOS LADOS Straightness of sides		± 0.5%	± 0.1%
	ORTOGONALIDAD Rectangularity		± 0.6%	± 0.1%
	PLANITUD DE LA SUPERFICIE Surface planarity		± 0.5%	±0.25%
	ABSORCIÓN DE AGUA Water absorption	UNE-EN-ISO 10545-3	≤ 0.5%	≤ 0.1%
	RESISTENCIA A LA FLEXIÓN Bending strength	UNE-EN-ISO 10545-4	MIN 35 N/MM2	52 N/MM2
	CARGA DE ROTURA Breakage load	UNE-EN-ISO 10545-4	MIN 1300 N	2000 N
	RESISTENCIA A LA ABRASIÓN PROFUNDA Deep abrasion resistance	UNE-EN-ISO 10545-6	MAX 175 MM3	120 MM3
	DILATACIÓN TÉRMICA Thermal expansion	UNE-EN-ISO 10545-8	METODO ENSAYO DISPONIBLE Test method available	
	RESISTENCIA AL HIELO Frost resistance	UNE-EN-ISO 10545-12	RESISTE Resistant	RESISTE Resistant
	RESISTENCIA A ATAQUES QUÍMICOS Resistance to chemical attack	UNE-EN-ISO 10545-13	RESISTE Resistant	RESISTE Resistant
	RESISTENCIA A LAS MANCHAS Resistance to staining	UNE-EN-ISO 10545-14	CONFORME A LAS NORMAS Complies with standards	CONFORME A LAS NORMAS Complies with standards