



ARIS

PRODUCT	COLOR / REF	SIZE	PACKING
	ARIS GARNET SKU# ESS-ARI-GAR	7.5x30cm (3"x12")	22 Pcs / Box 5,38 Sqft / Box 15 Lbs / Box 130 Boxes / Pallet 699.4 Sqft / Pallet
	ARIS GREEN SKU# ESS-ARI-GRE	7.5x30cm (3"x12")	22 Pcs / Box 5,38 Sqft / Box 15 Lbs / Box 130 Boxes / Pallet 699.4 Sqft / Pallet
	ARIS LATTE SKU# ESS-ARI-LAT	7.5x30cm (3"x12")	22 Pcs / Box 5,38 Sqft / Box 15 Lbs / Box 130 Boxes / Pallet 699.4 Sqft / Pallet
	ARIS SILVER SKU# ESS-ARI-SIL	7.5x30cm (3"x12")	22 Pcs / Box 5,38 Sqft / Box 15 Lbs / Box 130 Boxes / Pallet 699.4 Sqft / Pallet

ARIS

PRODUCT	COLOR / REF	SIZE	PACKING
	ARIS WHITE SKU# ESS-ARI-WHI	7.5x30cm (3"x12")	22 Pcs / Box 5,38 Sqft / Box 15 Lbs / Box 130 Boxes / Pallet 699.4 Sqft / Pallet

TYPE	Glazed Porcelain	APPLICATION	Indoors / Outdoors / Wall / Floor
DESCRIPTION	A glossy wall tile collection in a brick-like 7.5x30cm (3"x12") format. Thanks to its straight edges, it can be laid in staggered conventional style, in aligned rows or in a herringbone pattern. The tiles' surface has a concave appearance, accentuating their reflective capacity. Aris comes in a wide choice of colours (white, beige, grey, green and garnet), strongly evocative of traditional ceramic tiles.		
PRODUCT INSTALLATION	It is recommended for the product to be installed by a qualified professional. We do not recommend the use of adhesives based on epoxy resin. Read carefully instructions set by the manufacturer of the adhesive used.		
PRODUCT CARE	For initial and daily cleaning the use of a damp cloth and mild soap is recommended. Avoid using abrasive and acidic cleaning products.		
NOTE	To achieve the visual aspect of the product and given the artisanal procedure for production and raw materials used, pieces can represent variation in size, texture, design and shade. This is done deliberately to give the product a unique personality and unrepeatable characteristics.		





TECHNICAL SPECIFICATIONS	ISO	TEST METHOD	PASS/FAIL
 FROST RESISTANCE	ISO 10545-12	No Resist	Pass



WWW.THISISWW.COM

FACT SHEET

ARIS

SURFACE TECHNICAL SPECIFICATIONS		ISO	TEST METHOD	PASS/FAIL
	ACID & ALKALI RESISTANCE	ISO 10545-13	GLA/GLA	Yes
	CRAZING RESISTANCE	ISO 10545-11	Resists	Yes
	STAINING RESISTANCE	ISO 10545-14	5	Yes
	SURFACE QUALITY	ISO 10545-2	> 95%	Yes