



## **TEXTILE**

PRODUCT	COLOR / REF	SIZE	PACKING
	TEXTIL BLUE SKU# ESS-TEX-BLU	20x20cm (8"x8")	26 Pcs / Box 11.19 Sqft / Box 40 Lbs / Box 72 Boxes / Pallet 805.68 Sqft / Pallet
	TEXTIL DECOR SKU# ESS-TEX-DEC	20x20cm (8"x8")	26 Pcs / Box 11.19 Sqft / Box 40 Lbs / Box 72 Boxes / Pallet 805.68 Sqft / Pallet
	TEXTIL GREEN SKU# ESS-TEX-GRE	20x20cm (8"x8")	26 Pcs / Box 11.19 Sqft / Box 40 Lbs / Box 72 Boxes / Pallet 805.68 Sqft / Pallet
	TEXTIL GREY SKU# ESS-TEX-GREY	20x20cm (8"x8")	26 Pcs / Box 11.19 Sqft / Box 40 Lbs / Box 72 Boxes / Pallet 805.68 Sqft / Pallet



26 Pcs / Box 11.19 Sqft / Box

40 Lbs / Box

72 Boxes / Pallet 805.68 Sqft / Pallet



## PRODUCT COLOR / REF SIZE PACKING 26 Pcs / Box 11.19 Sqft / Box 40 Lbs / Box 72 Boxes / Pallet 805.68 Sqft / Pallet

20x20cm (8"x8")

TEXTIL PINK

SKU# ESS-TEX-PIN

**TEXTILE** 

TYPE	Glaced Porcelain	APPLICATION	Indoors / Outdoors / Wall / Floor	
DESCRIPTION	Inspired by the weave of fabrics, Textile features a subtle elegant mesh-like pattern made up of smaller meshes. The version with a white background features different overlapping layers of colour in randomly combined compositions, while the plain-coloured models come in the same background shade as the white version's overlapping colours, thus creating visual interplay evocative of different superimposed textile weaves.			
PRODUCT INSTALLATION	It is recommended for the product to be installed by a qualified professional. We do not recommend the use of adhesives based on epoxy resin. Read carefully instructions set by the manufacturer of the adhesive used.			
PRODUCT CARE	For initial and daily cleaning the use of a damp cloth and mild soap is recommended.  Avoid using abrasive and acidic cleaning products.			
NOTE	materials used, pieces can	ect of the product and given the artisanal procedure for production and raw in represent variation in size, texture, design and shade. This is done deliberation and unrepeatable characteristics.		





## **TEXTILE**

TECHN	ICAL SPECIFICATIONS	ISO	TEST METHOD	PASS/FAIL
**************************************	FROST RESISTANCE	ISO 10545-12	No Resist	Pass

	FACE TECHNICAL PECIFICATIONS	ISO	TEST METHOD	PASS/FAIL
	ACID & ALKALI RESISTANCE	ISO 10545-13	GLA/GLA	Yes
<b>}</b>	CRAZING RESISTANCE	ISO 10545-11	Resists	Yes
	STAINING RESISTANCE	ISO 10545-14	5	Yes
_	SURFACE QUALITY	ISO 10545-2	> 95%	Yes